

Seating Fabric Options

group13

STANDARD FABRICS



Ebony




Royal




Crimson




Mocha



Sandstone




Midnight



Tex Black

RECYCLED FABRICS




Indigo



Raven

TB133 FABRICS



Ebony



Royal



Crimson



Mocha



Sandstone

MORE FABRIC CHOICES ON THE NEXT PAGE. ➡

SELECTED SEATING FABRICS ARE AVAILABLE IN LIMITED QUANTITIES

THESE FABRICS ARE SPECIFIC TO THE CHAIR(S) YOU HAVE CHOSEN. THERE MAY BE AN ADDITIONAL CHARGE FOR OTHER CALPIA FABRICS. IF YOUR ORDER EXCEEDS AVAILABLE STOCK YOU MAY BE ASKED TO CHOOSE AN ALTERNATE FABRIC. TO VIEW ACTUAL FABRIC SWATCHES CONTACT YOUR SALES REPRESENTATIVE OR CALL OUR SHOWROOM AT (916) 323-2419.

Seating Fabric Specifications

FABRIC SPECS.	COMPANION STANDARD FABRICS (AZUL SCARLET PEBBLE)	INSIGHT STANDARD FABRICS (SUMMIT TEX BLACK MIDNIGHT PORT)	FOUNDATION STANDARD FABRICS (HUNTER BOULDER)	SEQUEL STANDARD FABRICS	CATALYST RECYCLED FABRIC	ICON RECYCLED TB133 FABRIC (RAVEN INDIGO)	TB133* FABRIC	CRYPTON® TREATED FABRIC
RECYCLED CONTENT								
Percentage	None	None	None	None	100% Recycled	100% Recycled	None	None
TECHNICAL INFO.								
Content	52% Nylon 48% Polyester	100% Polyester	100% Polyester	100% Polyester	100% Recycled Polyester	100% Recycled Polyester	100% Polyester	Base: 100% Polyester or 100% Recycled Polyester
Backing	Acrylic	Acrylic	SBR Latex	None	None	Acrylic	None	Cypton®*
Finish	None	Stain Resistant		Nano-Tex Stain Resistant	None	Teflon	Nano-Tex Stain Resistant	Cypton®* Antimicrobial Silver Ion Tech.
CLEANING INFO.								
Spot Clean	**WS = Water/ Solvent	**WS = Water/ Solvent	**WS = Water/ Solvent	**WS = Water/ Solvent	**WS = Water/ Solvent	**WS = Water/ Solvent	**WS = Water/ Solvent	Water
PERFORMANCE								
Surface Abrasion (Double Rubs)	ASTM-D-4157/4157 Exceeds 159,000 DR	Exceeds 192,000 DR	ASTM-D-3597 Exceeds 1,000,000 DR	ASTM-D-3597 Exceeds 288,000 DR	ASTM-D-3597 /4157 Exceeds 90,000 DR	Exceeds 400,000 DR	ASTM-D-3597 Exceeds 288,000 DR	Exceeds 243,000 DR (Cotton Duck)
Crocking dry/wet	(AATC8) Crocking Class 4/ Class 4	(AATC8) Crocking Class 4.5/ Class 4.5	(AATC8) Crocking Class 5/ Class 5	(AATC8) Crocking Class 4/ Class 4	(AATC8) Crocking Class 5/ Class 5	(AATC8) Crocking Class 5/ Class 5	(AATC8) Crocking Class 4/ Class 4	(AATC8) Crocking Class 4/ Class 3
Light (AATCC-16)	Exceeds 60 hours	Class 5 Exceeds 60 hours	Exceeds 40 hours	Class 4 Exceeds 60 hours	Class 5 Exceeds 60 hours	Class 4 Exceeds 60 hours	Class 4 Exceeds 60 hours	Class 5 Exceeds 60 hours
FLAMABILITY								
TB 117 Sec E (Class1-pass)	Passes	Passes	Passes	Passes	Passes	Passes	Passes	Passes
NFPA 260 (UFAC)-Class 1	Passes	Passes	Passes	Passes	Passes	Passes	Passes	Passes
TB133*	Yes (see below)	Yes (see below)	Yes (see below)	Yes (see below)	Yes (see below)		Yes (see below)	Yes (see below)

Cypton® is moisture, stain, odor, fungus, mildew bacteria resistant. Cypton®'s moisture barrier is integrated into the fabric, ensuring permanent protection. Cypton® is the first and only fabric approved by the EPA proven to be disinfectable.

*California Technical Bulletin 133 (TB133) refers to flammability test procedures for seating used in areas occupied by the public. Fabrics passing TB133 must be tested on the product to be certified as meeting TB133 for specific product information go to www.catalog.pia.ca.gov.


**Clean this fabric with the foam only of a water based cleaning agent for water based soiling, or with a pure solvent in a well-ventilated room (Petroleum distillate-based products, Energine, Carbona, Renuzit or similar products may be used) for oil-based stains only. Cleaning by a professional furniture cleaning service is recommended. To prevent overall soil, frequent vacuuming or light brushing to remove dust and grime is suggested.




California Prison Industry Authority • 560 East Natoma Street, Folsom CA 95630-2200 • 916-358-2733 • calpia.ca.gov

For more information visit our online catalog at: calpia.ca.gov or contact CALPIA Sales at: (916) 323-2419 or Customer service at 916 358-2733

Seating Fabric Options



Ebony



Royal




Crimson



Mocha



Sandstone



Midnight



Tex Black

THE INNOVATION OF CRYPTON® TREATED FABRIC


Crypton® is moisture, stain, odor, fungus, mildew bacteria resistant. Crypton®'s moisture barrier is integrated into the fabric, ensuring permanent protection.




Vinyl Seating Upholstery Options

VINYL OPTIONS


STANDARD



Black Sable



Navy Blue




Coffee Brown


TB133 HEALTH CARE VINYL OPTIONS




Cherry




Terra



Shamrock



Moonstone



Cosmic

SELECTED SEATING FABRICS ARE AVAILABLE IN LIMITED QUANTITIES

THESE VINYLs ARE SPECIFIC TO THE CHAIR(S) YOU HAVE CHOSEN. FOR TB133 OPTIONS PLEASE REFERENCE EACH SPECIFIC CHAIR. TO VIEW ACTUAL VINYL SWATCHES CONTACT YOUR SALES REPRESENTATIVE OR CALL OUR SHOWROOM AT (916) 323-2419.

VINYL SPECIFICATIONS ON THE NEXT PAGE. ➡

Vinyl Seating Upholstery Specs.

STANDARD GRADE VINYL

APPLICATIONS Office, Residential

GENERAL SPECIFICATIONS

WIDTH	54"
WEIGHT	1.27 lbs. per Linear Yard
BACKING	70% Polyester/30% Cotton

PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	200,000+ Double Rubs per ASTM D 4157- 02 Wyzenbeek / CFFA - 1A
MILDEW RESISTANCE	Pass ASTM G21-96 (2002) / CFFA-120
ANTI-BACTERIAL	Pass AATCC 147-2004 / CFFA-300
ANTI-MICROBIAL	Pass ASTM G21-96 (2002) / CFFA-120
ULTRA VIOLET RESISTANCE	Class 4/ 100 hrs. min
COLD CRACK	-20° F Federal Standard No. 191A Method 5874 / CFFA-6
STAIN RESISTANT	Yes
SULFIDE STAIN RESISTANT	Yes

FLAMMABILITY SPECIFICATIONS *

California Fire Code Technical Bulletin No. 117, Section E
BIFMA
UFAC Class 1
MVSS 302
NFPA 260
IMO A.652 (16) 8.2
IMO A.652 (16) 8.3
May Comply with California 133 when tested with suitable components
Can be treated to Pass FAA 25.853

* This term and any corresponding data refer to typical performance in the specific tests indicated and should not be construed to imply the behavior of this or any other material under actual fire conditions.



TB133 HEALTHCARE GRADE VINYL

APPLICATIONS Healthcare, Residential

GENERAL SPECIFICATIONS

WIDTH	54"
WEIGHT	28 Ounces per Linear Yard
BACKING	100% Brushed Polyester Knit

PERFORMANCE SPECIFICATIONS

ABRASION RESISTANCE	300,000+ Double Rubs per ASTM D 4157- 02 Wyzenbeek / CFFA - 1A
MILDEW RESISTANCE	Pass ASTM G21-96 (2002) / CFFA-120
ANTI-BACTERIAL	Pass AATCC 147-2004 / CFFA-300
ANTI-MICROBIAL	Pass ASTM G21-96 (2002) / CFFA-120
ULTRA VIOLET RESISTANCE	300 Hours ASTM G26-96 Method C / CFFA-2
COLD CRACK	-20° F Federal Standard No. 191A Method 5874 / CFFA-6
STAIN RESISTANT	with Resillience ^{SR} Protection
SULFIDE STAIN RESISTANT	

FLAMMABILITY SPECIFICATIONS *

California Fire Code Technical Bulletin No. 117, Section E
BIFMA
UFAC Class 1
MVSS 302
NFPA 260
IMO A.652 (16) 8.2
IMO A.652 (16) 8.3
May Comply with California 133 when tested with suitable components
Can be treated to Pass FAA 25.853



California Prison Industry Authority • 560 East Natoma Street, Folsom CA 95630-2200 • 916-358-2733 • calpia.ca.gov

For more information visit our online catalog at: calpia.ca.gov or contact CALPIA Sales at: (916) 323-2419 or Customer service at 916 358-2733

O 091214 01
R 061715 01